

J P Upholstery

Thank-you for your purchase. If you have received this seat cover lightly folded please lay flat for a few hours before fitting to eliminate any creases that may have occurred during transit.

Fitting Instructions

Work on a clean surface so that the new cover will not be damaged.

Remove the old seat cover.

Remove any old staples from seat base.

Check the foam in the seat and try to repair any large damage. If foam is wet, allow it to dry out completely before fitting new seat cover.

Put the new seat cover over the front of the seat and work your way over the whole seat to the rear.

Make sure the seat cover is situated straight over the seat. (There are cut notches indicating the centre of the seat cover)

BE CAREFULL THE STAPLES YOU ARE USING ARE NOT TOO LONG. (We recommend a maximum of 6mm)

Turn the entire seat with cover over. Install a couple of staples at the front and a couple at the back.

Warm the seat cover with a hair dryer or hot air gun. (The tighter you get the cover on the seat the better the finished results).

Pull the seat cover tightly and install a few staples around both sides.

Turn the seat back over and make sure the cover is still straight (Try to keep the seat cover warm to allow any stretching that may be required to keep a tight fit)

Continue stretching across the width of the seat, adjusting the staples if necessary.

Now install more staples around the front, back and sides, until there is at least one staple every 1 inch.

There are plenty of informative videos on youtube showing how to fit motorcycle seat covers which are worth viewing.