

JP Upholstery

Thank-you for your purchase. If you have received this seat cover lightly folded please lay flat for a few hours before fitting to eliminate any creases that may have occurred during transit.

Fitting Guide for Steel Based Seats

Work on a clean surface so that the new cover will not be damaged.

Remove the old seat cover by very carefully bending back the metal tabs in seat base to their open position.

Check the foam in the seat and try to repair any large damage. If foam is wet, allow it to dry out completely before fitting new seat cover.

If you have purchased our Scrim Foam then fit the scrim foam using the technique in our Scrim foam fitting guide.

Place the new seat cover over the front of the seat and work your way over the whole seat to the rear.

Make sure the seat cover is situated straight over the seat. (There are cut notches indicating the centre at each end of the seat cover)

Turn the entire seat with cover over. Start at the front by fixing the seat cover over a couple of tabs also fix a couple at the back. Bend the tab slightly to keep the seat cover retained.

TIP - if some of the tabs are blunt you may need a sharp blade to cut a small slit in the seat cover band

Warm the seat cover with a hair dryer or hot air gun. DO NOT allow the new seat cover to get too hot as damage may occur. Pull the seat cover tightly sideways around the central position and pull the seat cover over a couple of tabs both sides of the seat.

Turn the seat back over and make sure the cover is still straight. Try to keep the seat cover warm to allow any stretching that may be required to keep a tight fit. (The tighter you get the cover over the seat foam the better the finished results).

Adjust the seat cover if necessary.

Now work your way round starting from the front cheeks stretching from the centre of the cover outwards pulling the seat cover over the tabs.

Next move to the sides and then the back, until all of the tabs are used.

If you are happy the seat cover is fitted correctly then carefully close the tabs using a tack hammer or similar.

Visit us at: **www.motorcycleseatcovers.co.uk**